



TECHNICAL DATA

RR 125 4T MOTARD

CHASSIS

Frame	steel double cradle frame
Wheel base	1370 mm
Max length	2065 mm
Max width	820 mm
Max height	1230 mm
Seat height	920 mm
Ground clearance	310 mm
Footrest height	378 mm
Dry weight	103 kg
Fuel tank capacity	5,7 l.
Reserve	1 l.
Front suspension	Hydraulic fork with ø41 mm shaft
Rear suspension	Monoshock with adjustable spring preload
Shock absorber stroke	52 mm
Front wheel travel	250 mm
Rear wheel travel	205 mm
Front brake	disc ø260 mm
Rear brake	disc ø220 mm
Front rim	21 x 1,6 - 36 holes
Rear rim	18 x 1,85 - 36 holes
Front tyre	110/80-17
Rear tyre	130/70-17

ENGINE

Type	Single-cylinder, 4-stroke, air cooled
Bore	54,0 mm
Stroke	54,0 mm
Displacement	124cc
Compression ratio	10:1
Ignition	Electronic Moriyama F5HH
Spark plug	NGK R CR7 HSA
Lubrication	Forced with pump
Feeding	Unleaded gasoline
Carburettor	Mikuni UCAL 5Nh ø26-38
Clutch	Wet multi-disc clutch
Primary trasmission	Z. 20/68
Transmission	5 speed
Secondary trasmission	Z. 14/50
Engine oil	SAE 15W/50